

Handhelds Devices Settings (Handheld Commons)

The **Handhelds Devices** section in OPS-COM allows administrators to manage and configure handheld devices used for enforcement and data collection. This includes registering new devices, pushing messages, and updating device settings, ensuring seamless operation for field personnel and accurate data synchronization.

Using this Feature

1. Click **Tools**, then **Handhelds Devices**. Alternatively, you can access this on the **Violations** menu as well.
2. The **Handhelds - Common Settings** screen appears, where you can manage various aspects of your handheld fleet. From here, you can edit settings such as ticket due dates, customize ticket footers, view device information, and add or manage individual handheld units.

Adding a New Device

When adding a new handheld device, the process involves both the device itself and the OPS-COM system configuration.

1. **Install Software:** Start by installing the OPS-COM for Android software on the handheld device.
2. **Obtain UUID:** After the first login attempt on the device, you'll receive a notice indicating the device isn't registered. This message will display a **UUID** (Universally Unique Identifier) number. This is a 16-digit alphanumeric code typically found under your login screen on the device.
3. **Register Device in OPS-COM:**
 - Once on the **Handhelds - Common Settings** page in the admin portal, click **Add New Device**.
 - A new screen will open. You must add the following information:
 - **UUID:** Enter the UUID obtained from the handheld device.
 - **Server to Sync with: Always start by selecting the Production Server.** This is a critical step for initial device registration, regardless of whether the device will eventually be used for testing on a Preview server (explained further in "Important Note - Additional Information").

- **Name:** Enter a descriptive **name** to easily identify this device (e.g., "Patrol Unit 1," "Enforcement Officer John's Device").
- Ensure the **Enabled** checkbox at the top of the entry form is selected.
- Click **Add Device** once all information is in place.

Pushing Messages

You can send messages directly to your configured handheld units:

1. On the **Handhelds - Common Settings** screen, click the **Push Message** button.
2. Follow the prompts to compose and send your message to the selected devices.

Updating Device Data

To modify settings for an existing handheld device:

1. On the **Handhelds - Common Settings** screen, click on the **device name** you wish to update. This will open a drop-down list of editable settings.
2. Make your desired changes to the device's configuration.
3. Once finished, ensure you click **Process Updates** to save and apply your changes to the device.

Best Practices & Considerations

- **Production Server First (Crucial):**
 - **Important Note:** Due to the underlying logic of the Handheld Common tool, you **must always register a new handheld unit on the Production admin portal first**, even if its ultimate purpose is for testing on a Preview site.
 - The system initially connects to the production server, then references the `PA Common/handheld assignment` table (which is written from production) to determine if a unit is registered for Production or Preview. This ensures the correct routing is established in the database.
 - This initial production-side registration is also why you can refresh preview sites without losing the handheld units configured for them.
- **Adding a Handheld Unit to Preview for Testing:**
 1. First, add the handheld unit to **Handhelds - Common Settings** on the **production** admin portal as described in "Adding a New Device," but select your **Preview Server** in the **Server to Sync with** field. This sets the proper database route.
 2. Next, navigate to the **preview** admin portal and enter the exact same device information into its **Handhelds - Common Settings** section.
 3. Finally, perform a **reinstallation of the OPS-COM for Android software** on the handheld device itself. This reinstallation allows the handheld to pick up the newly set path to the preview server.
- **Switching Between Production and Preview:**

- Once a handheld entry exists in both Production (configured for Preview sync) and Preview, you can generally switch between environments by re-pointing the **Sync With** setting on both the Production and Preview admin portals to your preferred path.
 - **However, remember that you must perform a reinstallation of the software on the handheld unit each time you change the synchronization path in the system** for the handheld device itself to update with the selected path.
 - **UUID Accuracy:** Ensure the UUID is entered precisely, as any error will prevent the device from connecting.
 - **Descriptive Naming:** Use clear, identifiable names for your handheld devices to simplify management and troubleshooting.
-

Revision #7

Created 8 May 2024 08:33:30

Updated 18 June 2025 09:49:55 by Cedar Boulianne