

Importer Field Descriptions

Introduction

A list of all the columns used in the importer and a description of what the field is used for in the system.

- **Unique ID** fields are required, and are used to identify a record as being a unique entity in the system before it has been imported and an ID can be assigned to it.
 - They contain the bare-minimum information needed to import the record.
- **Recommended** fields are not technically required, and a record can be made without them, but they contain information that make the record a useful entity in the system.
 - This is information like the first and last names of a user or the value of the fine on a violation.
 - A record is able to exist in the system without these fields, but it won't do much without them.
- **Optional** fields are not required, and a record without them can still function as a useful entity in the system.
 - They contain supplemental information that can be filled in later or aren't needed for the basic functionality of the record, such as the year a vehicle was made.

Importer Columns

UserProfile Table

Column Name	Internal Name	Requirement	Type	Description
-------------	---------------	-------------	------	-------------

User Unique ID (UUID)	UserUUID	Unique ID <ul style="list-style-type: none"> This or Email is Required 	Standard	<p>The primary identifier. If UUID is not supplied, email will be used as the key identifier instead.</p> <p>This value identifies the user as a unique record and it or the email is required to import a record.</p>
Email Address	email	Unique ID <ul style="list-style-type: none"> This or UUID is Required 	Standard	<p>The secondary identifier. If UUID is not supplied, email will be used as the key identifier instead.</p> <p>This value identifies the user as a unique record and it or the UUID is required to import a record.</p>
Username	username	Recommended	Standard	The username of the user.
First Name	firstName	Recommended	Standard	The first name of the user.
Middle Name	middleName	Optional	Standard	The middle name of the user.
Last Name	lastName	Recommended	Standard	The last name of the user.
Password	password	Optional	Standard	The password of the user.
User Type	UserTypeID	Recommended	Foreign Key <ul style="list-style-type: none"> UserTypes Table 	<p>The user type of the user. Attaches to the UserTypes table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the TypeName column of the UserTypes table, as these are the values that will be matched against.</p> <p>The values in the uploaded file must be an exact match to the values in the TypeName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The UserTypeID from the UserTypes table matching the name will be inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
Street Address	street	Optional	Standard	The street address of the user.
City	city	Optional	Standard	The city of the user.

Province/ State	prov	Optional	Foreign Key <ul style="list-style-type: none"> Provinces Table 	<p>The province or state of the user. Attaches to the Provinces table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the ProvName column of the Provinces table, as these are the values that will be matched against. These are the long names of the province and not the abbreviation; as in, Ontario and not ON.</p> <p>The values in the uploaded file must be an exact match to the values in the ProvName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The ProvID from the Provinces table matching the name will inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
Postal Code	postal	Optional	Standard	The postal or ZIP code of the user.
Cellphone Number	phonecell	Optional	Standard	The cellphone number of the user.
Employee Number	employNo	Optional	Standard	The employee number of the user.
Student Number	studentNo	Optional	Standard	The student number of the user.
Secondary Phone Number	sPhone	Optional	Standard	The secondary phone number of the user.
Date of Birth	DOB	Optional	Standard	The date of birth of the user.
Preferred Name	preferredname	Optional	Standard	The preferred name of the user.
Public Comment	publicComment	Optional	Standard	The public comment for the user. Visible to the user.
Private Comment	privateComment	Optional	Standard	The private comment for the user. Not visible to the user.
Login Source	loginSource	Optional	Standard	<p>The method by which the user logs into the system.</p> <p>If a login source is not supplied for a user, it will be set to OPSCOM by default.</p>

OffenseLocations Table

For additional information on this table, refer to this article: <https://ops-com.atlassian.net/wiki/x/9ZYL>

Column Name	Internal Name	Requirement	Type	Description
Location Name	LocationName	Unique ID <ul style="list-style-type: none">Required	Standard	The name of the location being imported. This value identifies the location as a unique record and is required to import a record.
Writer Visible	WriterVisible	Optional	Standard	Whether the writer of a violation of a ticket made in the location is visible to the user.
GIS Number	GisNo	Optional	Standard	The GIS number is a geographic location code and is only used by certain clients. Associated with GIS maps (https://www.gismaps.org/).

Vehicle Table

Column Name	Internal Name	Requirement	Type	Description
Licence Plate	Plate	Unique ID <ul style="list-style-type: none">Required	Standard	The license plate number of the vehicle. This value identifies the vehicle as a unique record and is required to import a record.
Vehicle Year	Year	Optional	Standard	The year of the vehicle.
Active Vehicle	active	Optional	Standard	Indicates whether the vehicle is active or not. If not supplied, vehicles will be set to active by default.

Plate Type Name	PlateTypeID	Optional	Foreign Key <ul style="list-style-type: none"> VehiclePlateType Table 	<p>The plate type of the vehicle. Attaches to the VehiclePlateType table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the TypeName column of the VehiclePlateType table, as these are the values that will be matched against.</p> <p>The values in the uploaded file must be an exact match to the values in the TypeName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>TheTypeID from the VehiclePlateType table matching the name will inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
Province/State	ProvID	Optional	Foreign Key <ul style="list-style-type: none"> Provinces Table 	<p>The province or state of the user. Attaches to the Provinces table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the ProvName column of the Provinces table, as these are the values that will be matched against. These are the long names of the province and not the abbreviation; as in, Ontario and not ON.</p> <p>The values in the uploaded file must be an exact match to the values in the ProvName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The ProvID from the Provinces table matching the name will inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>

Vehicle Make Name	MakeID	Optional	Foreign Key <ul style="list-style-type: none"> VehicleMake Table 	<p>The make of the vehicle. Attaches to the VehicleMake table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the MakeName column of the VehicleMake table, as these are the values that will be matched against.</p> <p>The values in the uploaded file must be an exact match to the values in the MakeName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The MakeID from the VehicleMake table matching the name will inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
Vehicle Type Name	TypeID	Optional	Foreign Key <ul style="list-style-type: none"> VehicleType Table 	<p>The type of the vehicle. Attaches to the VehicleType table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the TypeName column of the VehicleType table, as these are the values that will be matched against.</p> <p>The values in the uploaded file must be an exact match to the values in the TypeName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The TypeID from the VehicleType table matching the name will inserted into the record in the base table.</p> <p>The value will be left blank in the imported record if no matches are found.</p>

Vehicle Colour Name	ColourID	Optional	Foreign Key <ul style="list-style-type: none"> VehicleColours Table 	<p>The colour of the vehicle. Attaches to the VehicleColours table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the ColourName column of the VehicleColours table, as these are the values that will be matched against.</p> <p>The values in the uploaded file must be an exact match to the values in the ColourName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The ColourID from the VehicleColours table matching the name will be inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
VIN Number	vin	Optional	Standard	The Vehicle Identification Number (VIN) of the vehicle.

Permits Table

Column Name	Internal Name	Requirement	Type	Description
Permit Number	PermitNo	Unique ID <ul style="list-style-type: none"> Required 	Standard	<p>This field is the first primary identifier. Both it and LotNameID must be provided to create a new permit</p> <p>This value identifies the permit as a unique record and is required to import a record.</p>

Lot Name (Long)	LotNameID	Unique ID <ul style="list-style-type: none">Required	Foreign Key <ul style="list-style-type: none">LotNames Table	<p>The long name of the lot associated with the permit. Attaches to the LotNames table.</p> <p>This field is the second primary identifier. Both it and PermitNo must be provided to create a new permit.</p> <p>This value identifies the permit as a unique record and is required to import a record.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the LotName column of the LotNames table, as these are the values that will be matched against. These are the long form version of the lot name, and not the lot short name.</p> <p>The values in the uploaded file must be an exact match to the values in the LotName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The LotNameID from the LotNames table matching the name will inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
Visible	visible	Optional	Standard	Indicates whether the permit is visible or not.
Permit Status	status	Optional	Standard	The status of the permit.
Permit State	StateID	Optional	Foreign Key <ul style="list-style-type: none">PermitState Table	The state of the permit.

Violations Table

Column Name	Internal Name	Requirement	Type	Description
Ticket Number	Ticket	Unique ID <ul style="list-style-type: none">Required	Standard	<p>The unique identifier for the violation.</p> <p>This value identifies the violation as a unique record and is required to import a record.</p>

Licence Plate	VehicleID	Recommended	Foreign Key <ul style="list-style-type: none"> Vehicle Table 	<p>The license plate number of the associated vehicle. Attaches to the Vehicle table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the Plate column of the Vehicle table, as these are the values that will be matched against.</p> <p>The values in the uploaded file must be an exact match to the values in the Plate column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The VehicleID from the Vehicle table matching the name will inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
Ticket Type Name	TicketType	Recommended	Foreign Key <ul style="list-style-type: none"> TicketCategory Table 	<p>The type of the ticket. Attaches to the TicketCategory table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the TicketTypeName column of the TicketCategory table, as these are the values that will be matched against.</p> <p>The values in the uploaded file must be an exact match to the values in the TicketTypeName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The TicketTypeID from the TicketCategory table matching the name will inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
Fine Amount	Fine	Recommended	Standard	The amount of fine associated with the ticket.
Towing Amount	Towing	Optional	Standard	The amount of towing charges associated with the ticket.
Tax Amount	taxAmount	Optional	Standard	The amount of tax associated with the ticket.
Issued Date	Issued	Recommended	Standard	The date the ticket was issued.
Due Date	Due	Recommended	Standard	The due date for payment of the ticket.
Ticket Writer	Writer	Optional	Standard	The admin who wrote the ticket.

Violation Location Name	LocationID	Recommended	Foreign Key <ul style="list-style-type: none">• OffenceLocations Table	<p>The name of the location where the violation occurred. Attaches to the OffenceLocations table.</p> <p>The values supplied by the user in the uploaded file are expected to be values from the LocationName column of the OffenceLocations table, as these are the values that will be matched against.</p> <p>The values in the uploaded file must be an exact match to the values in the LocationName column, matching the capitalization, spelling, and spacing exactly, or else it won't be counted as a match.</p> <p>The LocationID from the OffenceLocations table matching the name will inserted into the record in the base table. The value will be left blank in the imported record if no matches are found.</p>
-------------------------------	------------	-------------	--	---

Revision #1
Created 16 July 2024 09:28:01 by Nicole
Updated 11 June 2025 14:18:00 by Nicole