

OperationsCommander - <https://opscom.wiki>

## Push API: Permit Update

API access is a paid feature and must be granted by OPSCOM. Email your Account Executive to negotiate access.

The OPSCOM Controller provides a simple JSON based API to integrate with. Clients use this API to directly feed paid permit details into OPSCOM from other systems such as Parking Apps.

Make sure you set the HTTP Content-Type header to be application/json.

## Making API Requests

Raw Request:





```
POST
/api/OC-
TOMA/v1/p
ermits/up
date
HTTP/1.1
Host:
controlle
r.operati
onscomman
der.io
Accept:
applicati
on/json
Content-
Type:
applicati
on/json
Cache-
Control:
no-cache
```

```
{
  "apiToken
": "YOUR-
API-
TOKEN",
  "referenc
eID":
"PREVIOUS
-
REFERENCE
-ID",
  "plate":
"PL8RDR",
  "Amount":
"14.50",
  "currency
":
"CAD",
  "endTime"
```

JavaScript Request:





```
var  
request  
= new  
XMLHttpRe  
quest();
```

```
request.o  
pen(  
'POST'  
, '  
https://c  
ontroller  
.operatio  
nscommand  
er.io/api  
/OC-  
TOMA/v1/p  
ermits/up  
date');
```

```
request.s  
etRequest  
Header(  
'Content-  
Type',  
'applicat  
ion/json'  
);
```

```
request.s  
etRequest  
Header(  
'Accept'  
,  
'applicat  
ion/json'  
);
```

```
request.o  
nreadystatechange  
=  
function  
( ) {
```

# Request Object Attributes

<b>A</b>	<b>T</b>	<b>L</b>	<b>P</b>	<b>D</b>
<b>t</b>	<b>y</b>	<b>i</b>	<b>o</b>	<b>e</b>
<b>t</b>	<b>p</b>	<b>m</b>	<b>s</b>	<b>s</b>
<b>r</b>	<b>e</b>	<b>i</b>	<b>s</b>	<b>c</b>
<b>i</b>		<b>t</b>	<b>i</b>	<b>r</b>
<b>b</b>		<b>s</b>	<b>b</b>	<b>i</b>
<b>u</b>			<b>l</b>	<b>p</b>
<b>t</b>			<b>e</b>	<b>t</b>
<b>e</b>			<b>N</b>	<b>i</b>
			<b>a</b>	<b>o</b>
			<b>m</b>	<b>n</b>
			<b>e</b>	
			<b>s</b>	

a	S	5	a	(
p	t	0	p	<b>R</b>
i	r	-	i	<b>e</b>
T	i	c	T	<b>q</b>
o	n	h	o	<b>u</b>
k	g	a	k	<b>i</b>
e	r	e	r	<b>r</b>
n	a	n	e	<b>d</b>
	c	t	)	
	e	r	Y	o
	r	a	o	u
	l	p	r	s
	h	a	u	p
	n	u	p	p
	m	e	i	e
	r	i	d	A
	c	i	P	I
	n	c	T	o
	l	u	k	e
	d	i	n	.
	g	d	a	s
	d	a	s	h
	a	s	h	e
	s			s

R	S	5	r	(
e	t	0	e	<b>R</b>
f	r	-	f	<b>e</b>
e	i	c	e	<b>q</b>
r	n	h	r	<b>u</b>
e	g	a	e	<b>i</b>
n		r	n	<b>r</b>
c		a	c	<b>e</b>
e		c	e	<b>d</b>
I		t	i	)
D		e	d	
		r	r	T
		a	e	h
		l	f	i
		p	e	s
		h	r	v
		a	e	a
		n	n	l
		u	c	u
		m	e	e
		e	l	i
		r	D	s
		i	r	s
		c	e	u
		i	f	p
		n	e	p
		c	r	l
		l	e	i
		u	n	e
		d	c	d
		i	e	t
		n	_	o
		g	i	w
		d	d	h
		a		e
		s		n
		h		t
		e		h
		s		e
				n

E S 2 e (   
 n t 0 n O   
 d r - d p   
 D i c T t   
 a n h i i   
 t g a m o   
 e r e n   
 a E a   
 c n /   
 t d )   
 e D   
 r a M   
 s t u   
 Y e s   
 - U t   
 m t b   
 - c e   
 d i   
 \ n   
 T t   
 H h   
 : e   
 i f   
 : o   
 s r   
 f m   
 o a   
 r t   
 m o   
 a f   
 t Y   
 . -   
 m   
 -   
 d   
 \   
 T   
 H   
 :   
 i

L	S	2	p	(
i	t	5	l	O
c	r	-	a	p
e	i	c	t	t
n	n	h	e	i
s	g	a	L	o
e	r	i	n	
P	a	c	a	
l	c	e	/	
a	t	n	)	
t	e	c		
e	r	e	T	
	s	P	h	
		l	e	
		a	p	
		t	l	
		e	a	
			t	
			e	
			o	
			f	
			t	
			h	
			e	
			v	
			e	
			h	
			i	
			c	
			l	
			e	
			.	

A S 9 a ( mt - mO  
o r c o p  
u i h u t  
n n a n i  
t g r t o  
a A n  
c m a  
t o /  
e u )  
r n  
d t T  
e r  
c a  
i n  
m s  
a a  
l c  
t i  
o n  
a m  
o u  
n t  
T h  
i s  
m  
u s  
t c  
o n  
t

C	S	1	c	(
u	t	0	u	O
r	r	-	r	p
r	i	c	r	t
e	n	h	e	i
n	g	a	n	o
c	r	c	n	
y	a	y	a	
	c	C	/	
	t	u	)	
	e	r		
	r	r	C	
	s	e	A	
		n	D	
		c	,	
		y	U	
		I	S	
		D	D	

## Successful Response

The response will be a json object. The same reference id will be returned.

Content-Type: application/json

```
{
  "status":
  "success",
  "reference_id":
  "1a9b5375-
cb75-
4c71-
9939-
eeae550b0
9ac",
  "Internal
Reference
ID":
  "1a9b5375-
cb75-
4c71-
9939-
eeae550b0
9ac"
}
```

---

Take Command of Your Parking and Security - <https://OperationsCommander.com>

Revision #2

Created 9 October 2024 08:25:31

Updated 19 August 2025 09:25:14